

[処理水量表]

加藤式自動モノスクリーン Monoシリーズ

(1 / 2)

型式 - [目開]	機長	機幅	水路内幅	設置角	目開き (mm) / 処理水量 (m ³ /H) [浄水最大値]								動力 (kW)	重量 (kg)
	(mm)	(mm)	(mm)		2	2.5	5	10	20	30	40	50		
KM-200 S -□	867.5	253	300~	55°	25	28	39	-	-	-	-	-	0.1	33
KM-200 SR -□	867.5	253	300~	55°	25	28	39	-	-	-	-	-	0.025	21
KMA-200 S -□	867.5	253	300~	55°	-	-	-	38	45	47	49	50	0.1	33
KMA-200 SR -□	867.5	253	300~	55°	-	-	-	38	45	47	49	50	0.025	21
KM-200 M -□	1101.5	253	300~	55°	25	28	39	-	-	-	-	-	0.1	37
KM-200 MR -□	1101.5	253	300~	55°	25	28	39	-	-	-	-	-	0.025	26
KMA-200 M -□	1101.5	253	300~	55°	-	-	-	38	45	47	49	50	0.1	37
KMA-200 MR -□	1101.5	253	300~	55°	-	-	-	38	45	47	49	50	0.025	26
KM-200 L -□	1351.5	253	300~	55°	25	28	39	-	-	-	-	-	0.1	40
KM-200 LR -□	1351.5	253	300~	55°	25	28	39	-	-	-	-	-	0.025	29
KMA-200 L -□	1351.5	253	300~	55°	-	-	-	38	45	47	49	50	0.1	40
KMA-200 LR -□	1351.5	253	300~	55°	-	-	-	38	45	47	49	50	0.025	29
KM-250 S -□	867.5	303	350~	55°	32	38	53	-	-	-	-	-	0.1	34
KM-250 SR -□	867.5	303	350~	55°	32	38	53	-	-	-	-	-	0.025	22
KMA-250 S -□	867.5	303	350~	55°	-	-	-	48	56	59	61	62	0.1	34
KMA-250 SR -□	867.5	303	350~	55°	-	-	-	48	56	59	61	62	0.025	22
KM-250 M -□	1101.5	303	350~	55°	32	38	53	-	-	-	-	-	0.1	38
KM-250 MR -□	1101.5	303	350~	55°	32	38	53	-	-	-	-	-	0.025	27
KMA-250 M -□	1101.5	303	350~	55°	-	-	-	48	56	59	61	62	0.1	38
KMA-250 MR -□	1101.5	303	350~	55°	-	-	-	48	56	59	61	62	0.025	27
KM-250 L -□	1351.5	303	350~	55°	32	38	53	-	-	-	-	-	0.1	41
KM-250 LR -□	1351.5	303	350~	55°	32	38	53	-	-	-	-	-	0.025	30
KMA-250 L -□	1351.5	303	350~	55°	-	-	-	48	56	59	61	62	0.1	41
KMA-250 LR -□	1351.5	303	350~	55°	-	-	-	48	56	59	61	62	0.025	30
KM-300 S -□	867.5	353	400~	55°	40	46	64	-	-	-	-	-	0.1	35
KM-300 SR -□	867.5	353	400~	55°	40	46	64	-	-	-	-	-	0.025	23
KMA-300 S -□	867.5	353	400~	55°	-	-	-	58	67	71	74	79	0.1	35
KMA-300 SR -□	867.5	353	400~	55°	-	-	-	58	67	71	74	79	0.025	23
KM-300 M -□	1101.5	353	400~	55°	40	46	64	-	-	-	-	-	0.1	39
KM-300 MR -□	1101.5	353	400~	55°	40	46	64	-	-	-	-	-	0.025	28
KMA-300 M -□	1101.5	353	400~	55°	-	-	-	58	67	71	74	79	0.1	39
KMA-300 MR -□	1101.5	353	400~	55°	-	-	-	58	67	71	74	79	0.025	28
KM-300 L -□	1351.5	353	400~	55°	40	46	64	-	-	-	-	-	0.1	42
KM-300 LR -□	1351.5	353	400~	55°	40	46	64	-	-	-	-	-	0.025	31
KMA-300 L -□	1351.5	353	400~	55°	-	-	-	58	67	71	74	79	0.1	42
KMA-300 LR -□	1351.5	353	400~	55°	-	-	-	58	67	71	74	79	0.025	31

[処理水量表]

加藤式自動モノスクリーン Monoシリーズ

(2 / 2)

型式 - [目開]	機長	機幅	水路内幅	設置角	目開き (mm) / 処理水量 (m ³ /H) [浄水最大値]								動力	重量
	(mm)	(mm)	(mm)		2	2.5	5	10	20	30	40	50	(kW)	(kg)
MS-300 S -□	1000	430	500~	60°	-	-	63	75	87	95	95	100	0.1	42
MS-300 SR -□	1000	430	500~	60°	-	-	63	75	87	95	95	100	0.025	30
MS-300 M -□	1400	430	500~	60°	-	-	63	75	87	95	95	100	0.1	50
MS-300 MR -□	1400	430	500~	60°	-	-	63	75	87	95	95	100	0.025	38
MS-300 L -□	1800	430	500~	60°	-	-	63	75	87	95	95	100	0.1	57
MS-300 LR -□	1800	430	500~	60°	-	-	63	75	87	95	95	100	0.025	45
MS II -500 S -□	1000	628	650~	60°	-	-	107	135	149	143	158	158	0.2	82
MS II -500 M -□	1400	628	650~	60°	-	-	107	135	149	143	158	158	0.2	91
MS II -500 L -□	1800	628	650~	60°	-	-	107	135	149	143	158	158	0.2	101

□ 型式の□には、目開きが入ります。

動力 冠水型ギヤドモータ (標準仕様 三相200V)

0.2kW ・ 0.06kW ・ 0.04kW も御座います。